SAN SIMEON SHUTTER RULES

Tuesday, March 2, 2017.

- 1. All residences must have some form of approved hurricane protection installed on all windows, lanai sliding glass doors and glass block within 72 hours prior to the predicted arrival of a hurricane.
- 2. Approved hurricane protection cannot be installed more than 72 hours prior to the predicted arrival of a hurricane and must be removed within 72 hours after the passage of a hurricane.
- 3. Owners may paint their storm panels which were supplied at the time of purchase. The approved colors (which match the window trim color) are: DR Horton- cream Leavitt- beige
- 4. If an owner is part-time at their residence, it is the owner's responsibility to either contract a company to put up and take down their hurricane shutters within the approved timeframes as mentioned above or ask a neighbor, another owner or a friend/relative in the area to do the same.
- 5. Any owner who wishes to install hurricane/security shutters on the inside of their lanai screen, must submit the plans to the Architectural Control Board. for approval. The approved colors are: DR Horton Bronze Leavitt White
- 6. Owners who were approved by the the Architectural Control Board and installed hurricane/security shutters placed at the <u>inside</u> of the patio screen will be allowed to be put down at any time.
- 7. Lack of installing hurricane protection to the residence and thus causing damage to the residence is the owner's responsibility for all repair costs.